



## **SYLBOND FB150**

<b>DESCRIPTION</b>	Sylbond FB150 Waterproofing Membrane is designed for the waterproofing of exposed new flat roofs, parapets, box gutters and the joining of new extensions. Sylbond FB150 can also be used in the maintenance and refurbishing of existing flats roofs, etc.
<b>COMPOSITION</b>	The Sylbond FB150 membrane consists of a synthetic fibre mat, laminated to a reinforced pressure sensitive modified bitumen compound. The rolls are interleaved with a disposable release film.
<b>SAFETY</b>	Normal hygiene procedures. Wash hands thoroughly with soap and water or a proprietary hand-cleaner prior to eating or smoking. Launder contaminated clothing, gloves, etc.
<b>STORAGE</b>	Store in original containers in a cool dry place. Maximum recommended shelf life : 6 months.



**SYLBOND FB150 (cont.)**

TYPICAL PROPERTIES	TEST METHOD	DATA
<b>Adhesion</b> <ul style="list-style-type: none"><li>- To Primed Steel</li><li>- To Self</li></ul>	ASTM D1000 24hr ASTM D1000 24hr	2.5N/mm 2.0N/mm
<b>Resistance to Acids, Alkalis &amp; Salts</b>		Excellent
<b>Temperature Range</b> <ul style="list-style-type: none"><li>- For application</li><li>- For Service</li></ul>		+15C to 45C +5C to 65C
<b>Length</b>		15m (or to order )
<b>Width</b>		850mm (or to order )
<b>Core Size</b>		76mm I.D
<b>Thickness</b> <ul style="list-style-type: none"><li>- Backing</li><li>- Adhesive</li><li>- Total</li></ul>	ASTM D1000	300µm 1200µm 1500µm
<b>Weight</b>		1.6Kg/m <sup>2</sup>
<b>Recommended Primer</b>		Denso Bitumen Primer D

**Important**

Winn & Coales / Denso SA (Pty) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request.

Denso SA (Pty) Ltd operate a Quality Management System registered to ISO 9001:2008.

Head Office / Factory: 120 Malacca Road, Red Hill, Durban. P.O.Box 201259, Durban North, 4016, South Africa  
Tel: +27 (031) 569 4319 Fax: +27 (031) 569 4328 Email: bid@denso.co.za Website: www.denso.co.za