

DENSO ALUMINIUM WATERPROOFING TAPE

DESCRIPTION	<p>Denso Aluminium Waterproofing Tape is a waterproofing membrane, ideal for sealing of flashing, metal sheeting, water tanks, down pipes and gutters. Denso Aluminium Waterproofing Tape displays the following properties:</p> <ul style="list-style-type: none">- <i>Excellent resistance to weathering.</i>- <i>Impermeable to moisture and water vapour.</i>- <i>Non-hardening.</i>- <i>Permanently flexible.</i>
COMPOSITION	<p>The membrane consists of a pressure sensitive, polymer modified adhesive compound laminated onto a pure aluminium foil backing, interleaved with a disposable release film.</p>
SAFETY	<p>Normal hygiene procedures. Wash hands thoroughly with soap and water or a proprietary hand-cleaner prior to eating or smoking. Launder contaminated clothing, gloves, etc.</p>
STORAGE	<p>Store in original containers in a cool dry place. Maximum recommended shelf life : 6 months.</p>

DENSO ALUMINIUM WATERPROOFING TAPE (cont.)

TYPICAL PROPERTIES	TEST METHOD	DATA						
Adhesion <ul style="list-style-type: none"> - To primed Steel - To self 	ASTM D1000 ASTM D1000	Min 2.5N/mm Min 2.5N/mm						
Resistance to Cathodic Disbonding	ASTM G95	Excellent						
Resistance to Acids, Alkalis & Salts		Excellent						
Temperature Range <ul style="list-style-type: none"> - For application - For Service 		+15°C to 45°C -20°C to 65°C						
Length		2.5m, 5m, 10m (or to order)						
Width		75, 100, 150, 900mm (or to order)						
Core Size		76mm I.D						
Thickness <ul style="list-style-type: none"> - Backing - Adhesive - Total 		<table border="1"> <tr> <td>35µm</td> <td>35µm</td> </tr> <tr> <td>1165µm</td> <td>1465µm</td> </tr> <tr> <td>1200µm</td> <td>1500µm</td> </tr> </table>	35µm	35µm	1165µm	1465µm	1200µm	1500µm
35µm	35µm							
1165µm	1465µm							
1200µm	1500µm							
Weight		<table border="1"> <tr> <td>1.3Kg/m²</td> <td>1.5Kg/m²</td> </tr> </table>	1.3Kg/m ²	1.5Kg/m ²				
1.3Kg/m ²	1.5Kg/m ²							
Recommended Primer		Denso Bitumen Primer D						

Important

Winn & Coales / Denso SA (Pty) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request.

Denso SA (Pty) Ltd operate a Quality Management System registered to ISO 9001:2008.

Head Office / Factory: 120 Malacca Road, Red Hill, Durban. P.O.Box 201259, Durban North, 4016, South Africa
 Tel: +27 (031) 569 4319 Fax: +27 (031) 569 4328 Email: bid@denso.co.za Website: www.denso.co.za