

## DENSO BASECOAT KIT

**DESCRIPTION** Denso Basecoat Kit in conjunction with a suitable scrim is used to provide a tough protective outer coating over Denso Petrolatum Tapes and as the saturation coat on Denso Fabric Backed Tapes.

Features of the Basecoat Kit:

- Durable and Weatherproof
- Excellent flexibility
- Good resistance to moderate trafficking
- Application by brush or roller

**COMPOSITION** A two component hard wearing coating, consisting of a liquid portion containing synthetic polymers and waterproofing admixtures and a cementitious powder portion consisting of fine fillers

**SAFETY** Normal hygiene procedures. Wash hands thoroughly with soap and water or a proprietary hand-cleaner prior to eating. Launder contaminated clothing, gloves, etc.

**STORAGE** Store in original containers in a cool, dry place away from and sources of ignition. Recommended shelf life: 12 months

TYPICAL PROPERTIES	TEST METHOD	DATA
<b>Solids Content (%)</b>		33%
<b>Specific Gravity</b>		0.99
<b>Drying Time</b>		2 hours @ 25°C
<b>Flash Point</b>		38°C
<b>Temperature Range</b> <i>For Application</i> <i>For Service</i>		0°C to +50°C -30°C to +60°C
<b>Spread Rate</b>		1.3lt / m <sup>2</sup>

Important

Winn & Coales / Denso SA (Pty) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request.

Denso SA (Pty) Ltd operate a Quality Management System registered to ISO 9001:2008.

Head Office / Factory: 120 Malacca Road, Red Hill, Durban. P.O.Box 201259, Durban North, 4016, South Africa  
Tel: +27 (031) 569 4319 Fax: +27 (031) 569 4328 Email: bid@denso.co.za Website: www.denso.co.za