

DENSO FIRE RETARDANT TOPCOAT

DESCRIPTION

Designed to be used in conjunction with the Denso Steelcoat 400 & 500 systems as a U.V Topcoat and provide a fire retardant waterproof seal.

- Provides a complete vapour barrier.
- Does not brittle with age.
- Withstands extreme climatic conditions and severe atmospheric pollution.

COMPOSITION

Denso Fire Retardant is a one component water based compound which dries to form a durable elastomeric membrane.

SAFETY

Normal hygiene procedures. Wash hands thoroughly with soap and water or a proprietary hand-cleaner prior to eating. Launder contaminated clothing, gloves, etc.

STORAGE

Store in original containers in a cool, dry place away from and sources of ignition. Recommended shelf life: 12 months

TYPICAL PROPERTIES	TEST METHOD	DATA
Colour		White
State		Pasty Liquid
Solubility in water		Excellent
pH-Value @ 25°C		8.0
Solids content		60 (±1%)
Mass per litre		1.35kg
Spread rate		1m ² / lt
Recommended DFT		0.8-1.2mm
Drying time		3 hrs @ 25°C
Temperature Range <i>For Application</i> <i>For Service</i>		+10°C to +40°C +10°C to +120°C

Important

Winn & Coales / Denso SA (Pty) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request.

Denso SA (Pty) Ltd operate a Quality Management System registered to ISO 9001:2008.

Head Office / Factory: 120 Malacca Road, Red Hill, Durban. P.O.Box 201259, Durban North, 4016, South Africa
Tel: +27 (031) 569 4319 Fax: +27 (031) 569 4328 Email: bid@denso.co.za Website: www.denso.co.za