



DENSO PRIMING SOLUTION

DESCRIPTION Denso Priming Solution is a petrolatum based primer for all surfaces prior to the application of Denso petrolatum tapes and compounds.

COMPOSITION Denso Priming Solution is a solvent based solution of saturated petroleum hydrocarbons.

SAFETY Denso Priming Solution is flammable and should not be applied in the vicinity of naked flames or sources of ignition.

Avoid contact with the skin and the inhalation of vapours.
Always ensure adequate ventilation is provided.

Normal hygiene procedures. Wash hands thoroughly with soap and water or a proprietary hand-cleaner prior to eating and smoking. Launder contaminated clothing, gloves, etc.

STORAGE Store in original containers in a cool, dry place away from any sources of ignition. Recommended shelf life: 12 months

TYPICAL PROPERTIES	DATA
Specific Gravity	0.85
Solids Content	50%
Spread Rate	9m ² /litre
Dry Film Thickness	50 micron average
Viscosity BS/B4 CUP @ 25°C	55-70 seconds
Drying Time	60 minutes approx.
Flash Point	32°C minimum
Application Temperature Range	-20°C to 55°C

Important

Winn & Coales / Denso SA (Pty) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request.

Denso SA (Pty) Ltd operate a Quality Management System registered to ISO 9001:2008.