

DENSO PVC SELF ADHESIVE TAPE

DESCRIPTION Denso PVC Self Adhesive Tape is a plasticised PVC sheeting coated one side with pressure sensitive adhesive.

USES As an outerwrap for Denso Petrolatum Tapes, Densoclad and Densopol Bituminous Tapes to improve resistance to damage and electrical resistance. The PVC tape is also used as a floor marking tape.

SAFETY Normal hygiene procedures. Wash hands thoroughly with soap and water or a proprietary hand-cleaner prior to eating or smoking. Launder contaminated clothing, gloves, etc.

STORAGE Store in original containers in a cool, dry place. Recommended shelf life: 6 months
Wrapped pipe / fittings should not be left exposed to direct sunlight for longer than fourteen (14) days.

TYPICAL PROPERTIES	DATA
Colours	Yellow or Black
Breaking Load	3.5N/mm
Elongation	Min 150%
Tear Strength	11N
Adhesion <ul style="list-style-type: none">To self	8N/25mm
Thickness	140 μ \pm 2
Breakdown Voltage	16 Kv min
Temperature Range <ul style="list-style-type: none">For ApplicationFor Service	0 $^{\circ}$ C to 50 $^{\circ}$ C -5 $^{\circ}$ C to 60 $^{\circ}$ C
Roll Length	33m
Roll Widths	50mm, 75mm, 100mm 150mm (or to order)
Colours	Yellow or Black

Important

Winn & Coales / Denso SA (Pty) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request.

Denso SA (Pty) Ltd operate a Quality Management System registered to ISO 9001:2008.

Head Office / Factory: 120 Malacca Road, Red Hill, Durban. P.O.Box 201259, Durban North, 4016, South Africa

Tel: +27 (031) 569 4319 Fax: +27 (031) 569 4328 Email: bid@denso.co.za Website: www.denso.co.za