

CLADSEAL 1500

DESCRIPTION	Denso Cladseal 1500 is a roofing product used between side and end laps on roof sheets to prevent water, wind and dust ingress, especially on shallow pitch roofs.
COMPOSITION	The membrane consists of a pressure sensitive, modified bitumen compound. The rolls are interleaved with a disposable release films.
SAFETY	Normal hygiene procedures. Wash hands thoroughly with soap and water or a proprietary hand-cleaner prior to eating or smoking. Launder contaminated clothing, gloves, etc.
STORAGE	Store in original containers in a cool dry place. Maximum recommended shelf life : 6 months.

TYPICAL PROPERTIES	TEST METHOD	DATA
Adhesion <ul style="list-style-type: none">- To Primed Steel- To Self	ASTM D1000 24hr ASTM D1000 24hr	2.5N/mm 2.5N/mm
Resistance to Acids, Alkalis & Salts		Excellent
Temperature Range <ul style="list-style-type: none">- For application- For Service		+15C to 45C +10C to 65C
Length		7.5m
Width		12mm, 24mm (or to order)
Core Size		76mm I.D
Thickness		1500µm
Weight		1.5Kg/m ²
Recommended Primer		Denso Bitumen Primer D

Important

Winn & Coales / Denso SA (Pty) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request.

Denso SA (Pty) Ltd operate a Quality Management System registered to ISO 9001:2008).

Head Office / Factory: 120 Malacca Road, Red Hill, Durban. P.O.Box 201259, Durban North, 4016, South Africa
Tel: +27 (031) 569 4319 Fax: +27 (031) 569 4328 Email: bid@denso.co.za Website: www.denso.co.za