

DENSOCHROME PASTE

DESCRIPTION Densochrome Paste is a slack wax based paste used to prevent corrosion at bimetallic junctions and to protect busbars. Densochrome Paste displays the following characteristics:

- *Non-drying / Non-hardening.*
- *Impervious to water.*

COMPOSITION Densochrome Paste is a blend of slack wax, inert filler, passivizing agents and zinc chromate inhibitors. It contains no volatile organic components.

SAFETY Chromates are toxic by inhalation, ingestion and skin absorption. Thorough personal hygiene must be observed and contaminated waste, rags, etc. disposed of according to local by-laws.

For further information please refer to the safety data sheet:

STORAGE Store in original containers in a cool, dry place.
Recommended shelf life: 12 months

TYPICAL PROPERTIES	DATA
Solids Content	>98%
Specific Gravity	1.1
Nominal Coverage	2-5m ² /kg
Temperature Range <i>For Application</i> <i>For Service</i>	0°C to 70°C 0°C to 70°C

Important

Winn & Coales / Denso SA (Pty) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request.

Denso SA (Pty) Ltd operate a Quality Management System registered to ISO 9001:2008.

Head Office / Factory: 120 Malacca Road, Red Hill, Durban. P.O.Box 201259, Durban North, 4016, South Africa
Tel: +27 (031) 569 4319 Fax: +27 (031) 569 4328 Email: bid@denso.co.za Website: www.denso.co.za