

TILESAFE WATERPROOFING MEMBRANE

DESCRIPTION

Denso Tilesafe Waterproofing Membrane is a unique, heavy duty, cold applied, self-adhesive waterproofing membrane. Developed for use prior to the application of tiles. Denso Tilesafe Waterproofing Membrane provides complete protection from water damage to the substrate, as well as preventing leakages. Denso Tilesafe Waterproofing Membrane can be used in the following areas:

- *Shower walls and floors.*
- *Balconies.*
- *Patios.*
- *Balconies.*

COMPOSITION

The membrane consists of a woven glass fibre grid, laminated to a pressure sensitive, modified bitumen compound. The rolls are interleaved with a disposable release film.

SAFETY

Normal hygiene procedures. Wash hands thoroughly with soap and water or a proprietary hand-cleaner prior to eating or smoking. Launder contaminated clothing, gloves, etc.

STORAGE

Store in original containers in a cool dry place. Maximum recommended shelf life : 6 months.

TILESAFE WATERPROOFING MEMBRANE (cont.)

TYPICAL PROPERTIES	TEST METHOD	DATA
Breaking Strength	ASTM D1000	6N/mm
Elongation @ Break	ASTM D1000	15%
Adhesion		
- To Primed Steel	ASTM D1000 24hr	2.5 N/mm
- To Self	ASTM D1000 24hr	2.5 N/mm
Resistance to Acids, Alkalis & Salts		Excellent
Temperature Range		
- For application		+15C to 45C
- For Service		+5C to 65C
Length		20m
Width		1000mm
Core Size		76mm I.D
Thickness		1600µm
Weight		1.6Kg/m ²
Recommended Primer		Denso Bitumen Primer D

Important

Winn & Coales / Denso SA (Pty) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request.

Denso SA (Pty) Ltd operate a Quality Management System registered to ISO 9001:2008.

Head Office / Factory: 120 Malacca Road, Red Hill, Durban. P.O.Box 201259, Durban North, 4016, South Africa
 Tel: +27 (031) 569 4319 Fax: +27 (031) 569 4328 Email: bid@denso.co.za Website: www.denso.co.za